

OUR SHREDDERS OF THE ARJES COMPACT CLASS



When choosing the right machine, our customers are usually faced with the question of which shredder is right for their specific requirements. Therefore, we have divided our unique double-shaft shredders into three product lines to help you make the right decision.

Fields of application IMPAKTOR class

Waste Wood & Biomass





Construction & Demolition Waste

Find out more about our applications and tool shafts in the brochure **RECYCLING IS OUR GLOBAL SOLUTION**

PRODUCT LINE IMPAKTOR

In the IMPAKTOR class, mainly, contractors in the construction and demolition industry will find an extremely compact, flexible and robust shredder with the best price-performance ratio in the industry. However, plant operators wanting to enrich their business with a compact shredder are also well represented in this segment. The mobile shredder is characterised by its unique track system and hook lift combination, a revolutionary shaft quick-change system, an innovative SCU control system and a shaft design that continuously expands the machine's range of applications.

The stationary electric version of the double-shaft shredder is convincing in particularly difficult areas of application due to its high efficiency and low maintenance costs. The two shredder components, shredding unit and control unit, can easily be integrated into existing recycling plants or used as an invidual machine.

In addition to numerous possible uses for construction and demolition waste, both the mobile and stationary shredders are suitable for processing concrete and wooden railway sleepers, roots, waste wood, tyres, domestic and comercial waste and other materials.



IMPAKTOR 250 evo The highlights of the mobile compact class in detail

nil



TECHNICAL DATA

DIMENSIONS

Version	Track system and hook lift
Length (mm)	7.700 / 7.300 (Transport)
Width (mm)	2.300 / 2.300 (Transport)
Height (mm)	3.500 / 2.800 (Transport)
Total weight (kg)	14.000

DRIVE	EU	US	ROW*
Engine (Volvo Penta)	TAD 581 VE	TAD 572 VE	TAD 551 VE
Emission standard	EU Stage V	EPA Tier 4f	Stage 3A
Power (kW / HP)	129/175	160/220	129/175
Fuel capacity (I)	360		
Gearbox	Bonfiglioli		



DISCHARGE BELT

Discharge height (mm)	3.450
Width (mm)	800
Included	Over-belt magnet and water sprinkler system

SHREDDING UNIT	
Hopper volume (m ³)	2,25
Shaft length (mm)	1.500
Shaft diameter (mm)	680
Weight (kg / cassette)	2.000
Rotation speed (rpm)	11 – 35



Easy transportation to any work place

Due to the low basic weight and a hydraulically lowerable chassis, transportation is possible on a small truck or hook lift truck without special permissions.



Quick change system for shafts

Easy installation and quick removal of shafts for easier maintenance, refurbishment and changing of shaft type, which increases more productivity.



Mechanically adjustable side combs

The side combs can be opened or closed, depending on material and customer requirements; decreasing the output size or increasing the throughput rate.

IMPAKTOR 250 e-pu The highlights of the stationary compact class in detail



TECHNICAL DATA

DIMENSIONS	
Version	Stationary
Shredding Unit	
Length (mm)	3.300
Width (mm)	2.300
Height (mm)	3.200
Control Unit	
Length (mm)	2.600
Width (mm)	1.600
Height (mm)	2.700
Total weight (kg)	approx 15.000

DRIVE

Engine	Electric
Power (kW)	160
Gearbox	Bonfiglioli

SHREDDING UNIT	иліт	
Hopper volume (m³)	2,25	
Shaft length (mm)	1.500	
Shaft diameter (mm)	680	
Weight (kg / cassette)	2.000	
Rotation speed (rpm)	11 – 35	





Separate drive and control unit

Due to separate placement of the shredding and control unit (max 8 meters in between) there is significant less vibration to the control system. Additionally, dust and dirt are reduced.



Quick change system for tool shafts

Easy installation and quick removal of shafts, for easier maintenance, refurbishment and changing of shaft type, which increases productivity.



Mechanically adjustable side combs

The side combs can be opened or closed, depending on material and customer requirements; decreasing the output size or increasing the throughput rate.





ARJES GmbH Werksplatz 1 | D-36433 Leimbach

€ +49 (3695) 85 855-0
➡ +49 (3695) 85 855-14
∞ info@arjes.de
♦ www.arjes.de



CONVINCING ARGUMENTS

Shortens maintenance times, refurbishment and changing different shaft types for uninterrupted operation

- Maximum mobility in every situation Track system* and hooklift/multilift included as standard
- **Innovative SCU plug-and-play control** Predefined shredding programs that control rotation and speed of shafts for user-friendly operability

*only available for mobile machines

3

4

5

