


ROTARY ELECTRIC MOTOR VIBRATOR SPECIFICATIONS	
MODEL NO.: KEE-6-4	
QTY.: TWO (2)	NOM. RPM/OPER. FREQ.: 1800
H.P. EACH: 1/3	H.P. TOTAL: 2/3
AMPS @ 460V. EACH: .70	AMPS @ 460V. TOT.: 1.4
RECOMMENDED BEARING LUBRICANT: SHELL OIL ALVANIA #3	
INTERVAL: 2200 HRS.	AMOUNT: 30 GRAMS/BRG.
SEE ROTARY ELEC. MTR. VIBRATOR I.O.M. FOR ADDITIONAL INFO.	

3 UNITS REQUIRED
SGM P.O. 5664

- GENERAL NOTES:
1. MATERIAL OF CONSTRUCTION: MILD STEEL.
2. UNIT IS ASSEMBLED AND TESTED PRIOR TO SHIPPING.
3. ELECTRICAL INSTALLATION BY OTHERS.
4. ALL MILD STEEL IS PAINTED PPG ALKYD ENAMEL: SGM GREEN.

THIS DRAWING IS THE PROPERTY OF BEST PROCESS SOLUTIONS, INC. LOANED TO THE RECIPIENT WHO AGREES THAT IT SHALL NOT BE GIVEN OUT, COPIED, OR DUPLICATED FOR THE USE OF ANOTHER, BUT USED ONLY BY THE RECIPIENT FOR THE PURPOSE OF MAINTAINING THE EQUIPMENT TO WHICH IT REFERS.				UNLESS OTHERWISE SPECIFIED ALL DIMENSIONS ARE IN INCHES		 best process solutions, inc.		www.bpsvibes.com			
				DECIMALS: .X ± .06 .XX ± .015 .XXX ± .005		SURFACE FINISH: 125 ✓		ANGLES: ± 0° 30'			
				DRAWN BY: Bob		DATE: 6/16/2016		CUSTOMER: SGM MAGNETICS			
				CHECKED BY:		DATE:		TITLE: MODEL CFL-1848-6-4-2 VIBRATORY FEEDER WITH 75 CU.FT. HOPPER			
				ENGR BY:		DATE:		SCALE: 1" =1'-0"			
NO.		REVISION		BY:		DATE		DRAWING NUMBER: 1605-10236-5			
								SHEET 1 OF 1			
								REV. -			